Articles

Description


DAIHAN-brand[®] Premium Hotplate, "HP-20A" & "HP-30A", Ceramic-Coated Plate, up to 380°C, with Certi. & Traceability Built-in Linearity PWM Controller, High Temp. Uniformity, 180×180- or 260×260-mm Plate, CE Certified



180×180mm Plate-type Hotplate "HP-20A"



260×260mm Plate-type Hotplate "HP-30A"



- with Certificate & Traceability :
 - Controlled by Serial Number, Certificate, Delivery-information, and Traceable Data Base System
 - Excellent for Sample Drying and Most General Lab Heating Applications
 - Superior Temperature Uniformity : Less than 10% on the Plate at Ambient Temperature
 - CE Certified
 PL(Product Liability) Insurance
 - * Excellent for Sample Drying and most General lab Heating Applications
 - * Smart Design of Body made by Aluminum Die-Casting (HP-20A)
 - $\ast\,$ Superior Temperature Uniformity : Less than 10% on the Plate at Ambient Temperature
 - * Superior Linearity for Temperature Control by Specially Designed Control Circuitry (PWM control)
- * Ceramic Coated Plate Chemical / Acid Resistance

Specification

Plate Size(mm) & Models		180×180mm Plate-type "HP-20A"	260×260mm Plate-type "HP- 30A"
Material	Body	Powder Coated Aluminum	Powder Coated steel
	Plate	Ceramic Coated Aluminum (Chemical / Acid Resistance, Easy to Clean)	
Temp. Range & Uniformity		Max. 380 °C Temp., High Uniformity : Difference 10% less	
Heating Power/Consumption		600 W	1.2 kW
Controller		Superior Linearity PWM Controller	
Permissible Temp. & RH %		Ambient +5 ~ 50 °C, 85% RH	
Dimension & Weight		206 $ imes$ 307 $ imes$ h99mm, 2.8kg	286×387×h99mm, 3.3kg
Packing Size & Gross Weight		400×280×h200mm, 5 kg	430×320×200hmm, 5 kg
Power Supply & Cord/Plug*		1 Phase, AC 120 V, 60 Hz or AC 230 V, 50 / 60 Hz	

* Other Specifications are available upon Customer's Request.

Ordering Information

With 180×180mm Plate-type, "HP-20A" Hotplates

 DH.WHP03120
 Hotplate, "HP-20A", 230V

 DH.WHP02120
 , 120V

With 260×260 mm Plate-type, "HP-30A" Hotplates

DH.WHP03121 Hotplate, "HP-30A", 230V DH.WHP02121 , 120V

Optional Stand Rod & Holder/Clamp

 DH.WHP503011
 (1) Stand Rod, "RD100", Stainless steel, Non-screw

 ϕ 12.7 × L390mm, for "HP-30A/30D", "MSH-30A/30D"

 DH.WHP503036
 (2) Stand Rod, "RD200", Stainless steel, 1.5p screw

 ϕ 12 × L450mm, for "HP-20A/20D", "MSH-20A/20D", "MSH-50A/55A", "MSH-50D/55D" and "SMHS"

 DH.WHP503012
 (3) Holder / Clamp / Clip, "CL220", for Temp. Probe

Specialized Features

