




The field proven Alpha Series glovebox provide compact effective platforms for environmental control with excellent price to performance value. The Alpha Series is excellent for both production R&D applications. The glovebox is available in two sizes: one for projection welding applications and the other for seam sealing or general industrial use.

Straight-forward controls allow the operator to easily operate oven, vacuum and inert gas backfill controls.

KEY FEATURES

- Configurations available for integrated seam sealing, projection welding, or stand-alone industry use
- · Stainless steel construction with exterior epoxy finish for easy maintenance
- · Ergonomically designed safety glass viewing window with interior lighting
- Two glove ports with built-in armrests
- Antechamber to transfer tools and product into enclosure
- Standard oil-free vacuum pump with vacuum oven
- Optional vacuum bakeout oven
- · Easy access, clean antechamber
- Calibrated to NIST standards
- CE certification available

TYPICAL APPLICATIONS




TECHNICAL SPECIFICATIONS

Enclosure				
Double laminated safety glass				
2				
1/8 in (3.2 mm) welded seam stainless steel				
Manual set rotometer				
15-watt fluorescent (each chamber)				
208-240 volts, 50/60 Hz, single phase				
15 amps (no oven); 30 amps (with oven)				
60 psig				
Front-Loading Interchange				
Front-loading, flush type. Polycarbonate construction.				
11.25 in x 8 in x 8 in (28 cm x 20 cm x 20 cm)				
0 - 100 scfh (0 - 2.83 scmh)				
Adjustable rotometer				

Vacuum Bake Oven (Optional)			
Туре	304 electro-polished stainless steel construction		
Size (Internal) L x W x H	14 in x 7-5/8 in x 7-5/8 in (36 cm x 19 cm x 19 cm)		
Backfill rate	10 scfh (.283 scmh)		
Backfill pressure	4 in water column (10.16 cm water column)		
Maximum temp	125° C standard, 200°C optional		
Safety oven temp	Setpoint 25° C over oven temperature max. ±10°(factory set)		
Vacuum	Dry pump 830 mbars (standard) Oil rotary vane pump 5 x 10-2 mbars (40 mTor) (optional) Dry pump 1.2 x 10-1 mbars (90 mTor) (optional)		
Controls	Temp set control: Ambient -125° (200° C optional) Backfill: On/Off Vacuum: On/Off		
Door	Black anodized door with integrated lock		
Chilled water	Needed for 200° C optional oven		



Alpha series optional vacuum bakeout oven



Vacuum oven controller unit

OPTIONAL ACCESSORIES

Gas analyzers	Oxygen, helium, moisture	
Gas mixers	Manual set or automated for two and three gases	
Gas purification units	Manual or automated	
Water chiller	Portable water chiller (P/N 138-00019-003)	

WEIGHT & DIMENSIONS

	Seam sealing enclosure	Projection welding enclosure
Dimensions (L x W x H)	35 in x 44.5 in x 20 in (89 cm x 113 cm x 37 cm)	24 in x 33.5 in x 14.5 in (61 cm x 85 cm x 37 cm)
Weight	Will vary with selected options	Will vary with selected options



1820 S. Myrtle Ave. • Monrovia, CA 91016 US T: (626) 303-5676 • F: (626) 358-8048 info@amadamiyachi.com • www.amadamiyachi.com ISO 9001 Certified Company • 24/7 Repair Service: 1-866-751-7378

AMADA MIYACHI AMERICA, INC. **AMERICAS**

AMADA MIYACHI AMERICA (Midwest Office) Wixom, MI 48393 T: (248) 313-3078 midwestsales@amadamiyachi.com antonio.ruiz@amadamiyachi.com

AMADA MIYACHI AMERICA (Mexico Office) El Paso, TX 79925 T: (915) 881-8765 mxsales@amadamiyachi.com

AMADA MIYACHI DO **BRASIL LTDA.** Sao Paulo, Brasil T: +55-11-4193-3607 FUROPE AMADA MIYACHI **EUROPE GmbH** Puchheim, Germany T: +49 (0) 89 83 94 030

AMADA MIYACHI CO., LTD. Noda, 278-0016 Japan T: +81-31-8015-6810 sales@miyachi.com

AMADA MIYACHI SHANGHAI CO., LTD. Shanghai, China T: +86-21-6448-6000 jwu@msc.miyachi.com AMADA MIYACHI KOREA CO., LTD. Gyeonggi-do, Korea T: +82-4-7125-6177

dykim@mkc.miyachi.com AMADA MIYACHI TAIWAN CO., LTD.

Tainei Taiwan R O C T: +886-2-2585-0161 AMADA MIYACHI (THAILAND) CO., LTD. Samutprakarn, Thailand T: +66-2-170-5977 info@mtl.miyachi.com

MIYACHI | MIYACHI | UNITEK | P E G O

AMADA VIETNAM CO., LTD. Ha Noi. Vietnam T: +84-4-6261-4583

AMADA MIYACHI INDIA PVT., LTD. Bangalore, Karnataka T: +91-80-4092-1749 or +91-80-4092-3549

info@miyachiindia.com

MIYACHI EAPRO

follow us on: F L You

